

KLUDI RENON
Waschtisch-Einhandmischer 110
DN 15

Oberfläche:
39 mattschwarz

Waschtisch-Armatur
Einhebelmischer
1-Loch Montage
geschlossener Hebel, Metall
Strahlregler M18,5 PCA
Keramik-Kartusche mit Heißwasserbegrenzung
Durchflussmenge bei 3 bar 4,5 l/min.
flexible Druckschläuche G^{3/8} DVGW zugelassen
Schnell-Montagesystem
Push open Ablaufgarnitur G1^{1/4}

Technical drawing of the shower head assembly with dimensions:

- Overall height: 160
- Top arm width: 70
- Top arm length: 140
- Adjustable height range: 1-30
- Distance from top arm to shower head: 125
- Shower head diameter: Ø61
- Shower head height: 50
- Shower head connection: G1 1/4
- Shower head mounting plate width: 48
- Shower head mounting plate height: 110
- Shower head mounting plate distance from top arm: 125
- Shower head mounting plate connection: G 3/8
- Overall height from mounting plate to shower head: 515

The graph shows the relationship between flow rate I (l/min) and pressure p (bar) for a 1/2 inch diameter valve. The flow rate increases rapidly from 0 l/min at 0 bar to about 4.2 l/min at 0.5 bar, then more gradually to approximately 4.5 l/min at 2 bar, and remains constant at that level up to 5 bar.

Pressure p (bar)	Flow rate I (l/min)
0	0
0.5	~4.2
1.0	~4.4
2.0	~4.5
3.0	~4.5
4.0	~4.5
5.0	~4.5